



DETACHABLE RESTRICTOR


TYPE

HEAVY DUTY KEY RELEASE RESTRICTOR

BENEFIT


Key release restrictor stay for use with Sterling & Storm Balanced heavy duty hinges

- Tested to BS6375-2
- Can withstand a force in excess of 1000N when opened at the restricted position
- Austenitic 304* stainless steel for enhanced corrosion resistance
- Compatible with all Securistyle heavy duty hinges
- 12 year guarantee (details available on request)




▼ HEAVY DUTY FRICTION SLIDER

Stainless steel/ plastic composite slider to give maximum strength yet perform with the smoothest of action




▼ RELEASE KEY

Dedicated release key allowing the restrictor stay to be detached



▲ LOCKING PIN

Unique locking pin design allowing simple detachment / engagement of the restrictor stay



* Austenitic (was 304) stainless steel to BS EN 10088-2 Grade 1.4301 for enhanced corrosion resistance



Manufactured in the UK

Securistyle

Kingsmead Industrial Estate, Princess Elizabeth Way
Cheltenham, Gloucestershire GL51 7RE, UK

Rev 3 – Jan 2014 - ©

Tel: +44 (0) 1242 221200



Fax: +44 (0) 1242 228194/520828

E-mail: info@securistyle.co.uk

Website: www.securistyle.co.uk



PRODUCT SPECIFICATIONS



Part Number	Description	Dim 'A' (in/mm)	Dim 'B' (in/mm)	Boxed Qty
SDR4	4" Detachable Restrictor Assembly	4/101.6	5.9/150	50
SDR6	6" Detachable Restrictor Assembly	6/152.4	7.87/200	50
SDR8	8" Detachable Restrictor Assembly	8/203.2	7.87/200	50
SDR10	10" Detachable Restrictor Assembly	10/254	9.84/250	50
R7347	Release Key			10

PRODUCT SPECIFICATION

- Easy to fit no routing required
- Suitable for 16mm to 18mm cavity height
- Non handed product
- Keys are sold separately



BS EN ISO9001
Cert No. Q05105

Due to our policy of continual improvement we reserve the right to alter specifications without notice. It is the responsibility of the window manufacturer to ensure that the finished window meets the required performance and safety specification.

All transactions are subject to our standard conditions of supply, which are available on request

Ref: DRHD

Securistyle

Kingsmead Industrial Estate, Princess Elizabeth Way
Cheltenham, Gloucestershire GL51 7RE, UK

Rev 3 – Jan 2014 - ©

An ASSA ABLOY Group Brand

Tel: +44 (0) 1242 221200

Fax: +44 (0) 1242 228194/520828

E-mail: info@securistyle.co.uk

Website: www.securistyle.co.uk

ASSA ABLOY