Product details	Real 2	
Product segment	activPilot Concept	
Product segment	easyPilot Soleil	
Product segment	activPilot Concept C	

The activPilot standard

In developing activPilot we created all the solutions needed for the next-generation window fitting standard within a single system. An intelligent, clearly structured modular system with far less components than was previously typical, activPilot meets all requirements placed on a modern range of fittings. activPilot is suitable for any shape of window, any window material and any level of automation, from manual mounting to fully automated serial production. The high level of flexibility, the attractive auxiliary functions, the new locking system and the functional design all ensure that your business is perfectly geared today to meet your customers' needs and future requirements.

easy Pilot – the turn fittings that are popular all over the world

The comprehensive fitting range for turn windows from Winkhaus offers numerous solutions that are sought after particularly in international markets. The high level of operating convenience and the sturdy Winkhaus quality convince customers worldwide.

Specification

Component type	Mortice cremone
Window material	Aluminium wood plastic steel
Sash fitting groove	16 mm hardware groove
Mounting side	DIN left DIN right
Opening type / switch sequence	Turn Top tilt handle Lateral tilt handle
Backset	15.5 mm
Handle position	in the middle
Lockable	no
min. sash rebate height	920 mm
max. sash rebate height	1,319 mm
Number of locking points	3

Lock point design	
	Octagonal bolt
colour	Silver
Surface	
	Galvanised
Stroke direction	in the same direction
Drive Stroke	19
Clamping	yes
Connectable	no
Gearbox design	one piece
Anti-Lift Device	no
Packaging	Reusable

Mortice drive

The mortice drive is mounted in the fitting groove which requires a cut-out in the window sash for the gear case. The drive unit is switched via the window handle and transmits the movement of the handle to all other components of the window fitting, so that the window can be brought into its various positions.

Note

For the intended use, please take into account the information from the fitting lists, mounting instructions and application diagrams. All rights and modi